

Foldable Touch POS TP-1560Sx

Foldable Design with Solid Aluminum Housing
15.6" Touch TFT LCD POS
Powerful Performance Intel Celeron J6412



TP-1560Sx Specifications

Screen	15.6" Touch TFT LCD (Resolution 1366 x 768) with Capacitive Touch Resolution 1920x 1080 IPS with Capacitive Touch Screen as option
CPU	Intel Celeron J6412, 2.00 GHz, Cache 4MB
Memory	DDR4 4GB as standard, 8GB as option ; Storage: mSATA SSD128GB as standard, 256GB as option
OS / Power Supply	Win 10/11, Linux Power supply: AC 100-240V/1.7A, Output DC12V 5A, 2-pin Connector with Lock (internal)
In/Out Ports	USB2.0 x4 , USB3.0 x2 , COMx2, RJ45x1, Type-C x1, HDMI x1, LAN 10/100/1000Mbps, Audio: 1xLine Out,1xMIC In, DC Jack 12V, RJ-12 Cash Drawer Jack
Environment	Operating temperature & humidity: 0°C - 40°C , 20%~80% Storage temperature & humidity : -20°C - 60°C , 20%~85%
Dimension/Weight	Product Size: 370 (W) x 230 (D) x 285 (H) mm Net Weight: 3.15 Kg Gross Weight: 3.8kg Packing Size: 425 (W) x 405 (D) x 260 (H) mm Volume Weight: 12Kg
Option	Customer Display (2 x 20 VFD or 2 x 20 LCD) , 11.6" LCD Second Display, 15.6" LCD Second Display CPU: Intel Core i3 / i5, MSR , Wi-Fi , Speaker, I-button